



# Model: SP-700 (230v model)

Gas-Fired Wood-Burning Rotisserie Smoker

## Approximate Smoker Capacities

(Capacities will vary based on physical shape, weight, and method of loading for each product specified.)

	Standard	Opt 1
Pork Butts (8-10 lbs)(3.6 - 4.5 kg) each.....	84 pieces	88
St. Louis Ribs (2.75 lbs)(1.2 kg) each.....	72 pieces	96
Whole Chicken (3-4 lbs)(1.4 - 1.8 kg) each.....	96 pieces	168
Beef Brisket (12-15 lbs)(5.4 - 6.8 kg) each.....	24 pieces	48



Standard - 12" Deep  
 (6) 3-tier, 3 1/2" (89mm) spacing, hanger assemblies  
 72 ft<sup>2</sup> (6.69 m<sup>2</sup>) cooking surface



Option 1 - 18" Deep  
 (4) 3-tier, 4 1/2" (114mm) spacing, hanger assemblies  
 72 ft<sup>2</sup> (6.69 m<sup>2</sup>) cooking surface

## Standard Features:

- Stainless steel construction; exterior and interior.
- Mineral wool insulated cabinet.
- Adjustable 16 1/4" (413mm) tall steel pipe legs.
- Front or rear flue configuration.
- Low velocity convection fan with 12" (305mm) fan blade (spare blade included).
- Control with a digital cook and hold thermostat ((140° to 325°F)(60° to 163°C), allows for selection of cook temperature, cook time, and hold temperature), and a pneumatic rotisserie advance foot switch.
- Interior light.
- 2" (51mm) grease drain with ball valve.
- (18) 12" x 48" (305 x 1219mm) nickel chrome plated product racks (see illustration above).

## Optional Features:

- Mirror image (left side - firebox; right side - gear motor, burner and utility connections).
- Glass product display doors and manual light switch.
- Optional rack hanger system (Option 1)- (4) 3-tier, 4 1/2" (114mm) spacing hanger assemblies with (12), 18" x 48" (457 x 1219mm) product racks.
- Stainless steel product racks.
- Smoke extractor damper (typically utilized in through the wall direct venting applications).
- Working height locking casters.
- Trailer package.
- Additional optional accessories are available.

Southern Pride Distributing, LLC  
 401 S Mill St  
 Alamo, TN 38001  
 Phone: 731.696.3175  
 Fax: 731.696.3180  
 www.southernpride.com

REVISED: July 2018


An ongoing program of product improvement may require us to change specifications without notice.

Serial number: P70A0275 to Current

© 2018 Southern Pride Distributing, LLC

# Model: SP-700 (230v model)

## Gas-Fired Wood-Burning Rotisserie Smoker




**Front View**

**Standard leg locations** (center to center) -  
52 1/4"W x 73"D (1327 x 1854mm)


**Optional front recessed leg locations** (center to center) -  
52 1/4"W x 61"D (1327 x 1549mm), front legs recessed 12"

### Mirror Image Unit -

All features switch sides.



**Back View**



**Top View**

### REQUIREMENTS

#### GAS

1/2 inch gas inlet (NPT)

150,000 BTU (44 KW) - Natural (NG)

Supply line pressure - 4.5" W.C. min - 10.0" W.C. max (11.2 - 26.5 mbar)

#### OR

150,000 BTU (44 KW) - Propane (LP)

Supply line pressure - 11.0" W.C. min - 13.0" W.C. max (27.4 - 32.4 mbar)

#### ELECTRICAL

230 volt AC, 50 hertz, 1-phase, 15 amp wiring required

Electrical cord and plug not provided

#### VENTILATION

The smoker must be vented in accordance with the Owner's Manual and the installation must comply with all relevant local and national codes and in a manner acceptable to the authority having jurisdiction.

SHIPPING (crated) - 2,230 lbs (1012 kg), Class 100

87"H x 81"W x 106"D (2210 x 2057 x 2692mm)

#### Minimum Clearance Requirements from Combustible Material

Back.....18" (457 mm)

Firebox door side.....24" (610mm)

Top.....18" (457mm)

Gear motor side.....18" (457mm)

Front.....48" (1219mm)

NOTE: If provision is made for service access, gear motor side and back clearance can be reduced to 2" (51mm). Through the wall insulation kit allows for 0" clearance on contact surface with combustibles.